Model Key Guide
4000 Series Stainless Steel Angle Valve

4000 Series

Gate & Bonnet Seals
1 = Viton® gate and bonnet
2 = Viton® gate / copper bonnet

Flange Type - 4th digit
0 = CF-F port with UNF thread
1 = ANSI, small OD
2 = ANSI, large OD
3 = KF/ISO-F bolted
4 = CF-F port with metric thread
5 = JIS flanges
6 = ISO-K clamped

0 4 5 1 2 - 0 1 5 0 R

Actuator Type
1 = Manual
2 = Pneumatic (DN 63 to 630)
5 = Spring loaded (DN16 - 50)

Solenoid Voltage
0 = No Solenoid
1 = 24 VDC
2 = 120 VAC
3 = 220 VAC
4 = 24V AC

Angle Valve Size ID - 3 digits

006 = .625”	060 = 6.0”
010 = 1.0”	080 = 8.0”
015 = 1.5“	100 = 10.0”
020 = 2.0”	120 = 12.0”
025 = 2.5”	160 = 16.0”
030 = 3.0”	200 = 20.0”
040 = 4.0”	250 = 25.0”

Position Indicator Type
R = Reed switch
X or Blank = No position indicator

HVA, LLC
12880 Moya Blvd., Reno NV 89506

www.highvac.com
sales@highvac.com

Toll free: (800) 551-4422
Fax: (775) 359-1369